

MINI EXCAVATOR | 16C-1 / 18Z-1 / 19C-1 / 19C-1 PC



STAGE V

OPERATING WEIGHT
1479 – 1868kg

ENGINE POWER
11.7kW

BUCKET TEAROUT
15.6kN / 18kN

CHOOSE TOUGH.

Hydraulic hoses are routed through the kingpost, boom and dipper to protect against site damage. Top-mounted boom ram reduces the risk of damage when loading.



CHOOSE GOOD DESIGN

Full width, cast rear counterweight and 100% steel panels protect against knocks, with inexpensive repairs.



CHOOSE EASY.

Pre-start checks are easier than ever with an external sight glass to check hydraulic oil levels and a quick to view analogue hour meter.



CHOOSE CLOSE CONTROL

All controls are close to hand, with two-speed tracking operated by a dozer lever button.

CHOOSE QUICK.

Utilise a quick turnaround with easy-to-clean sloping undercarriage, fast changeover of attachments and easy transportation with 10 tie-down points.



CHOOSE TO SUIT

Choose a premium or rental spec, zero or conventional tailswing, and cab or canopy.



CHOOSE VALUE.

Our new generation minis are designed with your profits in mind with a simple, classic design, low cost maintenance and easy repairs.



CHOOSE EFFICIENT

The Perkins 403J-07 diesel engine is Stage V compliant, without needing a DPF or AdBlue.

CHOOSE SAFE & SECURE.

Thatcham approved immobiliser*, with remote pin code management, eliminates unauthorised starts. Optional LiveLink provides added security.



CHOOSE PEACE OF MIND

For additional safety, our unique 2GO hydraulic isolation system, prevents accidental machine movements.



*Region specific

MINI EXCAVATOR | 16C-1 / 18Z-1 / 19C-1 / 19C-1 PC



SPECIFICATION.

| MODEL | 16C-1 | 18Z-1 | 19C-1 | 19C-1 PC |
|-----------------------------|-------------|--------|-------------|-------------|
| Bucket tearout | 15.6kN | 18kN | | |
| Service intervals | 500 hours | | | |
| Transport length | 3860mm | 3547mm | 3860mm | 3862mm |
| Height over cab (canopy) | 2342mm | 2340mm | 2345mm | 2345mm |
| Width over tracks (retr.) | 980mm | | | |
| Transport weight canopy/cab | 1545/1655mm | 1655mm | 1736/1816mm | 1769/1849mm |



STANDARD FEATURES.

- 500 hour greasing intervals
- 100% steel body panels
- Cast rear counterweight
- 100% flat cab glass
- Unique 2GO system
- Fully bushed kingpost
- 30mm bucket pins
- Electro-proportional controls
- ROPS/FOPS compliant cab
- Optional LiveLink



KEY FACTS **16C MINI EXCAVATOR**

**Choose JCB's Next Generation
Stage V Mini Excavators**

I-2T MINI EXCAVATORS

FIND OUT MORE



JCB

www.jcb.com